



USED OIL ACCEPTANCE CRITERIA*

Test	Test Method	Criteria		
		Min	Target	Max
Appearance	Visual check	--	Report	--
Density (g/ml - lb/gal)	D4052	--	Report	--
Water by Karl Fisher , % wt	ASTM D6304	--	5	15 **
Flash Point (PMCC), °F	ASTM D93	140	--	--
PCBs, ppm	GC-ECD	--	--	< 2
pH value	pH meter	--	Report	--
Phosphorus, ppm	ASTM D5185	--	--	1500
Sulfur, ppm	ASTM D5185	--	--	5500
Total Chlorine, ppm	ASTM D5185	--	--	1000 ***
Arsenic, ppm	ASTM D5186	--	--	5
Cadmium, ppm	ASTM D5185	--	--	2
Chromium, ppm	ASTM D5185	--	--	10
Lead, ppm	ASTM D5185	--	--	100
Silicon, ppm	ASTM D5185	--	100	250 ****
Vanadium, ppm	ASTM D5185	--	Report	--
Nickel, ppm	ASTM D5185	--	Report	--
Titanium, ppm	ASTM D5185	--	Report	--

UMO-BTAC01 - Revision : 03/01/2024

Notes:

- * - Used Oil as defined by 40 CFR Part 279 - Blue Tide Customer Profile Required
- ** - Criteria may be waived by Management on a case by case basis
- *** - If >1000 ppm Chlorine must pass rebuttable presumption per 40 CFR 279 (b)(1)(ii)
- **** - Criteria may be waived by Management on a case by case basis